

ELECTRIC STRIKE 005

APPLICATION

For use in replacement installations in wood jambs and iron gates Use with bored cylindrical locksets having up to 5/8" throw.*

FEATURES

FACE PLATE – 1-3/8" X 3-1/2"
 DURABILITY – 500,000 Life cycles
 HOLDING FORCE – 1000 lbs.
 SCRATCH & CORROSION RESISTANT FACE PLATE
 SOLID CAST LATCH – Chrome Plated
 Cavity Depth - 1/2"; Width - 9/16";
 Height - 1- 5/8"
 NON-HANDED
 HEAVY DUTY LATCH SPRING
 MORTISE TYPE – Backset 2-3/4" Deep
 FAIL SECURE – (Standard Action) Unlocks When Energized
 ONE-PIECE RELEASE MECHANISM – (U.S. Patent #4,984,835)

FINISH (Specify When Ordering)

BRASS - Powder Coated (005)
 SATIN CHROME - US26D (005C)

ELECTRICAL CHARACTERISTICS**

Four Magnetic Coils Available
 Color coded wires depict the voltage of each coil.

8-16 VAC/4-6 VDC (Standard Voltage):
 2 Black Wire Leads
 12 VDC: 1 Red Wire Lead, 1 White Wire Lead
 24 VAC: 2 Red Wire Leads
 24 VDC: 1 Black Wire Lead, 1 White Wire Lead

FAIL SECURE NORMALLY LOCKED (Unlocked when energized)

VOLTAGE	CURRENT/AMPS	OHMS	SOUND	DUTY
8-16 VAC/4-6 VDC	1.3-2.7	1.4	Buzz	Intrm.
12 VDC	.40	30.0	Silent	Intrm./Cont.
24 VAC	1.40	4.7	Buzz	Intrm.
24 VDC	.19	125.0	Silent	Intrm./Cont.

FAIL SAFE (Reverse Action) NORMALLY UNLOCKED (005RS)
 (Locked When Energized) Continuous Duty DC Coil which is energized for longer than one minute. Add RS to catalog number when ordering

VOLTAGE	CURRENT AMPS	OHMS	SOUND	DUTY
12 VDC	.40	30.0	Silent	Intrm./Cont.
24 VDC	.19	125.0	Silent	Intrm./Cont.



*5/8" throw is based on 1/8" door gap

**Specify voltage when ordering

COMPATIBLE LOCKSETS

ACCURATE	66
ARROW	C, H, M
BEST	5, 7, 50, 6TDL
CORBIN	1400-5600, 6100-6600
DEXTER	DEXLOCK, DURALOCK
DOMINION	300, 400, 5000
GUARD	1990
FALCON	A, BA, D, E, F, N
HARLOC	49/5900, 6900
KWIKSET	400-500, 582, 583
LOCKWOOD	900
LORI	80/8200, 81/8300,
MARKS	110
LSDA	1000-1500, 100-150
NATIONAL	400
PDQ	SR, SV, SX
PARKER	160A
RUSSWIN	3400, 4300
SARGENT	6, 7, 8, 9, 10
SCHLAGE	A, F
TACO	ED, HV, LXV, SV
TAYMOR	28
UNICAN	6000, 7004
WEISER	A, BA, D, E
WESLOCK	ALL LOCKS
YALE	5200, 5300

NOTE: Compatible lockset designations are offered as a convenience only; reference should be made to manufacturers catalogs for complete data as to exact requirements. Caution must be taken in the alignment of locks with latchbolts when used with an electric strike. The spacing between the door and door jamb varies. If the gap is exceptionally tight, the latchbolt may not project to its maximum length. Trine Products Company, assumes no liability for differences between items compared.



ACCESS CARDS • ACCESS CONTROL SYSTEMS • CREDIT CARDS
 EMBOSSED • I.D. BADGES • MEMBERSHIP CARDS



005